

AMALIE

Better than it has to be®
Since 1903



PRO ELITE

FULL SYNTHETIC

SAE 70

RACING OIL

With MOLY

BENEFITS:

AMALIE Pro Elite Racing Oil 70 will provide the following benefits when compared to products designed for normal passenger car use or many competition racing oils.

- » Increased Horsepower
- » Increased Wear Protection
- » Increased Shear Stability at High Temperature and High Load
- » Increased Resistance to Oxidative Breakdown



MADE IN U.S.A.



Better than it has to be[®]
Since 1903

PRO ELITE FULL SYNTHETIC RACING OIL With MOLY

AMALIE Pro Elite Racing Oil 70 employs a unique combination of synthetic base stocks and a proprietary mixture of organic and inorganic friction modifiers designed to **increase horsepower without sacrificing protection**. **AMALIE Pro Elite Racing Oil 70** resists the effects of cylinder “wash-down” and oil thinning due to its high inherent film strength and shear stable viscosity. A proprietary combination of Molybdenum, ZDDP, and organic as well as inorganic chemistry reduce friction under high load-high temperature conditions while providing top-class protection to all moving parts.

AMALIE Pro Elite Racing Oil 70 is designed specifically for multi-platform racing applications and is compatible with engines fueled by alcohol, nitromethane, diesel, and leaded or unleaded gasoline of all octane ranges including those boosted by nitrous oxide. It is designed to flow quickly at engine start-up to protect all moving parts and to resist thermal breakdown at increased temperatures.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------------|-----------|
| Kinematic Viscosity @100°C, cSt..... | 42.0 |
| Kinematic Viscosity @40°C, cSt..... | 350.0 |
| Viscosity Index..... | 175 |
| Color..... | Amber 4.5 |
| Specific Gravity..... | 0.87 |
| Flash Point, °C..... | 240 |
| Pour Point, °C..... | -24 |
| Cold Crank @(-10°C) cP..... | 3,200 |
| Zinc, ppm..... | 2050 |
| Molybdenum, ppm..... | 400 |

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

PRO ELITE FULL SYNTHETIC RACING OIL With MOLY

| VISCOSITY | PACK SIZE | PART # |
|-----------|----------------|--------------|
| 70 | 55 Gallon Drum | 160-65723-05 |

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

APPLICATIONS

AMALIE Pro Elite Racing Oil 70 is designed specifically for racing applications and is not formulated for engines employing catalyst type emission systems.

Additional Information

Please use proper handling and care that you would use with any motor oil. Contact your Sales Representative for SDS.