

AMALIE[®]

*Better than it has to be[®]
Since 1903*



MULTI-PURPOSE
HYPOID GEAR
GL-5 LUBRICANT

SAE
75W

BENEFITS:

- » Excellent EP and Anti-Wear Properties
- » Strong Resistance to Oxidation
- » Protects Against Rust and Corrosion
- » Excellent Demulsibility
- » Compatibility with Seal Materials



MADE IN U.S.A.



**MULTI-PURPOSE
HYPOID GEAR
SAE 75W
GL-5 LUBRICANT**

AMALIE Hypoid Gear Multi-Purpose GL-5 75W Gear Oil is a premium gear lubricant designed for passenger vehicles and light-duty commercial axles, and final drives. Features include excellent thermal and oxidation stability, compatibility with seal materials, water separation, foam suppression, and superior storage stability.

Check owner's manual for specific recommendations.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	75W
Kinematic Viscosity @100°C, cSt.....	6.5
Kinematic Viscosity @40°C, cSt.....	42
Viscosity Index.....	105
Flash Point, °C (°F).....	218 (424)
Pour Point, °C (°F).....	-42 (-43)
Density, S.G.....	0.87
Brookfield Viscosity, -40°C, cP.....	75,000

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

RECOMMENDATIONS

AMALIE Hypoid Gear Multi-Purpose GL-5 75W Gear Oil is recommended for gear boxes and transaxles that call for GL-5 gear oil.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

HYPOID GEAR LUBE MP

VISCOSITY	PACK SIZE	PART #
75W	16 Gallon Keg	160-73117-16

The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.