

AMALIE

Better than it has to be®
Since 1903



MARINE

SAE 40

30 TBN ENGINE OIL



MADE IN U.S.A.



Better than it has to be[®]
Since 1903

MARINE 30 TBN ENGINE OIL

AMALIE Marine Engine Oil SAE 40 - 30 TBN is a marine engine oil that meets the requirements of medium speed trunk piston engines used as the main propulsion and auxiliary engines on deep-sea vessels, as main propulsion engines on coastal and river ships, and in stationary power applications. **AMALIE Marine Engine Oil SAE 40 - 30 TBN** is designed to meet the needs of engines operating on heavy fuel. It is recommended for use in the latest model high power 2 and 4 cycle diesel engines. This oil is especially beneficial in engines having low crankcase oil consumption, or operating with low cylinder liner temperatures, and with fuels having moderate sulfur contents. The **AMALIE Marine Engine Oil SAE 40 - 30 TBN** is formulated to provide excellent resistance to thermal degradation, and to promote a high level of engine cleanliness and protection against wear. It has good resistance to oxidation and viscosity increases over long operating periods. Relatively high alkalinity reserves in the oils provide superior protection, neutralizing strong acids resulting from elevated sulfur fuels that find access to the crank case to promote oil degradation, ring, cylinder, and bearing corrosion. The oil is formulated to eliminate under crown deposits, reduce piston ring belt deposits, and maintain camshaft spaces and crankcase cleanliness. It contains the industry leading thermal and oxidation stability for long oil life and good oil consumption control. This oil provides outstanding lube/fuel compatibility

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

SAE Grade.....	40
TBN, mgKOH/g.....	30
API Gravity.....	25.5
Flash Point, °C.....	240
Kinematic Viscosity @100°C, cSt.....	13.5
Kinematic Viscosity @40°C, cSt.....	130.0
Viscosity Index.....	100
Pour Point, °C.....	-18
Sulfated Ash (%M).....	4.0

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

MARINE - 30 TBN

VISCOSITY	PACK SIZE	PART #
40	55 Gallon Drum	160-69643-05

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.