

AMALIE

Better than it has to be®
Since 1903



Diesel • Gasoline • Natural Gas

XLO Ultimate

Multi-Fuel

FORTIFIED WITH
MOLYBDENUM

SAE 15W-40

MOTOR OIL

Cummins CES 20092/API: CK-4/SN

BENEFITS:

- » High Soot Handling and Improved Sludge Control
- » Excellent Piston Cleanliness
- » Superior Protection for Valve Trains and Cylinder Liners
- » Increased Oxidation Stability
- » One Oil for Mixed Fleets
- » Exceptional Oil Consumption Control
- » Lasting TBN Retention

AMALIE ALAS+ (AMALIE Lubricant Analysis System) is AMALIE's used oil analysis program designed exclusively for AMALIE XLO and AMALIE XLO Ultimate customers. It allows them to get an inside look at what is going on in their engine. ALAS+ measures wear metals, contaminants, viscosity and other used oil characteristics to help prevent component failure, determine optimum drain intervals and help to reduce fuel costs. ALAS+ is a comprehensive analysis program using the most modern laboratory equipment available, that provides valuable information about your engine's condition every time the oil is changed for the life of the equipment. ALAS+ supplies clear concise analytical reports in a timely fashion that include the necessary data needed to help you successfully manage your highly expensive equipment investment.



MADE IN U.S.A.



AMALIE XLO Ultimate Multi-Fuel with Moly 15W-40 is a blend of premium conventional base stocks and the latest in engine oil additive technology to offer the ultimate protection for your engine. Designed to meet or exceed the latest specifications including Cummins CES 20092 for natural gas fueled engines, API CK-4 requirements for diesel fueled engines, and API SN for gasoline engines. It is also backwards compatible to previous OEM and API specifications such as CJ-4, CI-4, CI-4+, SM, SL, and CES 20085. This oil is also designed to protect EGR/Low-Emission Diesel Engines while maximizing the durability of Diesel Particulate Filters (DPF's).

AMALIE XLO Ultimate Multi-Fuel with Moly 15W-40 provides multi-fuel convenience without performance compromise and is recommended for use in a wide range of heavy-duty applications and operating environments found on-and off-highway, including engines operating under heavy loads. It is formulated for extended service/extended drain when operated under typical operating conditions. **AMALIE XLO Ultimate Multi-Fuel** oils offer improved TBN retention, lower oil consumption, greater wear protection, oxidation stability, excellent shear stability, and reduced high temperature deposits.

Always consult your vehicle's owner's manual when selecting the appropriate viscosity and service grade.

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Viscosity Grade.....	15W-40
Kinematic Viscosity @100°C, cSt.....	15.90
Kinematic Viscosity @40°C, cSt.....	118.0
Viscosity Index.....	143
Flash Point, °C (°F).....	215 (419)
Pour Point, °C (°F).....	-36 (-33)
Density, S.G.....	0.879
Sulfated Ash, Wt%.....	0.9
TBN, mgKOH/g.....	10.0

Typical values are listed. Variations not affecting the performance of this fluid may occur during production; however, these variations will not fall outside of set specification parameters.

Please consult AMALIE Technical Services or your local representative for a full listing of applications.

Technical Services: • (800) 368-1264 • techservices@amalie.com

XLO ULTIMATE MULTI-FUEL

VISCOSITY	PACK SIZE	PART #
15W-40	55 Gallon Drum	160-64803-05

Always refer to your vehicles operating manual to select the correct grade of oil for your engine. The data presented herein are believed to be accurate; however, Amalie Oil Company shall not be liable for its content and makes no warranty with respect thereto.

Health and Safety

Safety Data Sheets (SDS) are available from your sales representative or at AMALIE.com.

APPLICATION CHART

SPECIFICATIONS	XLO Ultimate 15W-40
ACEA	
E9, E7	✓
Allison	
TES 439	✓
API	
CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4	✓
SN, SM, SL, SJ	✓
Caterpillar	
ECF-3, ECF-2	✓
Cummins	
CES 20092, 20086, 20085	✓
Daimler (MB)	
MB 228.31	✓
Detroit Diesel	
DFS 93K222, 93K218, 93K216	✓
Deutz	
DQC III-10 LA	✓
WSS M2C171-F1	✓
Global	
DHD-1	✓
JASO	
DH-2, DH-1	✓
Mack	
EOS-4.5, EO-O Premium Plus, EO-N	✓
MAN	
M 3775, M3271-1	✓
Mil-PRF	
2104 Rev. H	✓
MTU	
2.1	✓
Navistar	
TSI-99-12	✓
Renault	
RLD-4, RLD-3	✓
Volvo	
VDS-4.5, VDS-4	✓